Eaton CH221DU

Eaton Bussmann series low voltage cylindrical fuse holder, 125 A, 690 V, Single-pole, DIN rail, 2 x M4 Panel mounting screws, CH22, 22 x 58 mm

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse holder
CATALOG NUMBER	CH221DU
UPC	051712685375
PRODUCT LENGTH/DEPTH	77 mm
PRODUCT HEIGHT	123 mm
PRODUCT WIDTH	36 mm
PRODUCT WEIGHT	155.333 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60269-2 EAC IEC 60269-1 UL Listed File E14853

Powering Business Worldwide

□□□□	
USED WITH	C22G, C22M, FWP-(amps)A22F fuses
AMPERAGE RATING	125 A
NUMBER OF POLES	Single-pole
WIDTH IN NUMBER OF MODULAR SPACINGS	2
BUILT-IN DEPTH	51.5 mm
FUSE SIZE	22 x 58 mm
OPERATING TEMPERATURE DETAILS	-20°C to +70°C
VOLTAGE RATING AT AC	690 V a.c. (IEC) and 700 V a.c. (UL)
VOLTAGE RATING AT DC	1000 V d.c. (IEC)
FUSE TYPE	C22G C22M
LOCKABLE	Yes
ACCESSORIES	JV-L Multipole connector kit, CH22-CTP IP20 Protection accessory, CH22-SPS Microswitch to work with CH221D(I)U
TORQUE RATING	Min 4 Nm/ Max 5 Nm
CONCURRENTLY SWITCHING N-NEUTRAL	No
MATERIAL	Polyester
OPTICAL DEFECT INDICATION	No
MOUNTING METHOD	DIN rail 2 x M4 Panel mounting screws
DEGREE OF PROTECTION	IP20
VOLTAGE RATING	690 V
TYPE	Fuse holder
APPLICATION	Industrial and Commercial applications
MODEL	CH22

□□	
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-holder-declaration-of-conformity-uk251073en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□