# Eaton CH223DU

Fuse accessory, Fuse-holder, low voltage, 125 A, AC 690 V, 22 x 58 mm, 3P, IEC, UL, C22M and C22G fuses, IEC 60269-1, IEC 60269-2, IP20

| | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series low voltage cylindrical fuse holder |
| **CATALOG NUMBER** | CH223DU |
| **UPC** | 051712685450 |
| **PRODUCT LENGTH/DEPTH** | 77 mm |
| **PRODUCT HEIGHT** | 123 mm |
| **PRODUCT WIDTH** | 107 mm |
| **PRODUCT WEIGHT** | 291 g |
| **COMPLIANCES** | CE Marked<br>RoHS Compliant |
| **CERTIFICATIONS** | IEC 60269-2<br>EAC<br>IEC 60269-1<br>UL Listed File E14853 |

Powering Business Worldwide

| □□□□ | |
|---|---|
| **USED WITH** | C22G, C22M, FWP-(amps)A22F fuses |
| **AMPERAGE RATING** | 125 A |
| **NUMBER OF POLES** | Three-pole |
| **WIDTH IN NUMBER OF MODULAR SPACINGS** | 6 |
| **BUILT-IN DEPTH** | 51.5 mm |
| **FUSE SIZE** | 22 x 58 mm |
| **OPERATING TEMPERATURE DETAILS** | -20°C to +70°C |
| **VOLTAGE RATING AT AC** | 690 V a.c. (IEC) and 700 V a.c. (UL) |
| **VOLTAGE RATING AT DC** | 1000 V d.c. (IEC) |
| **FUSE TYPE** | C22G<br>C22M |
| **LOCKABLE** | Yes |
| **ACCESSORIES** | JV-L Multipole connector kit, CH22-CTP IP20 Protection accessory, CH22-TPS Microswitch to work with CH223D(I)U |
| **TORQUE RATING** | Min 4 Nm/ Max 5 Nm |
| **CONCURRENTLY SWITCHING N-NEUTRAL** | No |
| **MATERIAL** | Polyester |
| **OPTICAL DEFECT INDICATION** | No |
| **MOUNTING METHOD** | DIN rail<br>2 x M4 Panel mounting screws |
| **DEGREE OF PROTECTION** | IP20 |
| **VOLTAGE RATING** | 690 V |
| **TYPE** | fuse accessory |
| **APPLICATION** | Industrial and Commercial applications |
| **MODEL** | CH22 |

| □□ | |
|---|---|
| DECLARATIONS OF CONFORMITY | eaton-low-voltage-cylindrical-fuse-holder-declaration-of-conformity-uk251073en.pdf |

| | |
|---|---|
| □□□□: | |
| □□□□: | |
| □□□: | |
| □□: | |

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□