# Eaton FCF15RN

Eaton Bussmann Series UL Class CF, FCF fuse, fast-acting, single-element cube fuse, 15 A, non-idicating fuse, interrupting rating of 50 kA at 600 Vdc and 300 kA at 600 Vac

| | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series FCF fuse |
| **CATALOG NUMBER** | FCF15RN |
| **UPC** | 051712362450 |
| **PRODUCT LENGTH/DEPTH** | 1.88 in |
| **PRODUCT HEIGHT** | 1.75 in |
| **PRODUCT WIDTH** | 0.75 in |
| **PRODUCT WEIGHT** | 0.08 lb |
| **COMPLIANCES** | CE Marked |
| **CERTIFICATIONS** | UL Listed<br>CSA Certified |

Powering Business Worldwide

## □□□□□

| | |
|---|---|
| **AMPERAGE RATING** | 15 A |
| **FREQUENCY RATING - MAX** | 60 Hz |
| **FREQUENCY RATING - MIN** | 50 Hz |
| **INTERRUPT RATING** | 300 kAIC at 600 Vac<br>50 kAIC at 600 Vdc |
| **RESPONSE TIME** | 4 min at 200% |
| **VOLTAGE RATING** | 600 Vac, 600 Vdc |

## □□□□□□

| | |
|---|---|
| **COLOR** | Black |
| **FUSE TYPE** | Class CF<br>Fast acting |
| **MATERIAL** | Glass filled PES |
| **NUMBER OF ELEMENTS** | 1 |
| **OPERATING TEMPERATURE** | -40° to 80°C |
| **PACKAGING TYPE** | Standard |
| **TERMINAL MATERIAL** | Electroless tin plated copper alloy terminal |

## □□□□

| | |
|---|---|
| **CLASS** | Class CF |
| **CONNECTION** | Blade end |
| **FUSE INDICATOR** | Non-indicating |
| **SPECIAL FEATURES** | Superior overload and cycling capabilities |
| **USED WITH** | TCFH30N, CCP2-3-30CF |

## □□

| | |
|---|---|
| □□□□: | |
| □□□□: | |
| □□□: | |
| □□: | |


□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com



© 2026 □□ □□□□□□□□


□□□□□□□□□□□□□□□□□□□□□□□□□□□□