# Eaton 170M1319

Fuse-link, high speed, 160 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, aR, DIN, IEC

| □□□□ | |
|---|---|
| **PRODUCT NAME** | Eaton Bussmann series high speed square body fuse |
| **CATALOG NUMBER** | 170M1319 |
| **UPC** | 051712216555 |
| **PRODUCT LENGTH/DEPTH** | 105 mm |
| **PRODUCT HEIGHT** | 46 mm |
| **PRODUCT WIDTH** | 300 mm |
| **PRODUCT WEIGHT** | 131 g |
| **COMPLIANCES** | CE Marked<br>RoHS Compliant |
| **CERTIFICATIONS** | UL Recognized<br>IEC Rated |

Powering Business Worldwide

| □□□□ | |
|---|---|
| **AMPERAGE RATING** | 160 A |
| **BREAKING CAPACITY** | 200 kA |
| **FUSE INDICATOR** | None |
| **INSULATED METAL GRIPPING LUGS (IMGL)** | No |
| **UTILIZATION CATEGORY** | aR (accompanied semiconductor protection) |
| **VOLTAGE TYPE** | AC |
| **FUSE SIZE** | 000 |
| **RATED VOLTAGE AC** | 690 V |
| **CENTER-TO-CENTER DISTANCE OF CONNECTIONS** | 76.7 mm |
| **CURRENT TYPE** | AC |
| **MOUNTING DIMENSION** | M8 |
| **CLASS** | Class aR |
| **CLEARING (I2T)** | 16000 at 660 V |
| **WATT LOSSES** | 32 W |
| **FUSE SHAPE** | Square body, slotted offset bolted tags |
| **PRE ARC (I2T)** | 2300 |
| **COLOR** | None |
| **INTERRUPT RATING** | 200 kAIC |
| **CONNECTION** | Blade end x blade end |
| **CONSTRUCTION SIZE** | 000 |
| **PACKAGING TYPE** | Standard |
| **VOLTAGE RATING** | 690 V (IEC), 700 V (UL) |
| **TYPE** | Fuse |
| **APPLICATION** | Semiconductor, DC Common bus, DC drives, power converters/rectifiers |
| **FUSE TYPE** | DIN 43653<br>U/80 Without indicator<br>Bolted tag |
| **FUSE SYSTEM (ACCORDING TO IEC 60269)** | Other |

| □□ | |
|---|---|
| DECLARATIONS OF CONFORMITY | eaton-high-speed-square-body-fuse-declaration-of-conformity-uk250927en.pdf |

| | |
|---|---|
| □□□□: | |
| □□□□: | |
| □□□: | |
| □□: | |

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□