Eaton 170M3958

Eaton Bussmann series high speed square body fuse, 250 A, AC 1000 V, compact size 1, 43 x 61 x 74 mm, aR, IEC, UL, type K indicator

PRODUCT NAME	Eaton Bussmann series high speed square body fuse
CATALOG NUMBER	170M3958
UPC	051712678834
PRODUCT LENGTH/DEPTH	61 mm
PRODUCT HEIGHT	72.5 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	956 g
CERTIFICATIONS	CE

Powering Business Worldwide

□□□□	
AMPERAGE RATING	250 A
BREAKING CAPACITY	100 kA
FUSE INDICATOR	Non Indicating
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	1*
RATED VOLTAGE AC	1000 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	74 mm
CURRENT TYPE	AC
MOUNTING DIMENSION	M10
CLASS	Class aR
CLEARING (I2T)	57000 at 1000 V
WATT LOSSES	55 W
FUSE SHAPE	Square Body size 1* to 3, flush-end contact
PRE ARC (I2T)	9550
COLOR	None
INTERRUPT RATING	125 kAIC
FITTED WITH:	Type K Indicator for micro
CONNECTION	Flush-end contact
CONSTRUCTION SIZE	1
MOUNTING METHOD	Flush
PACKAGING TYPE	Standard
VOLTAGE RATING	1000 V
TYPE	Square Body flush-end contact BKN/- Type K indicator for microswitch
APPLICATION	DC common bus DC drives power converters/rectifiers reduced voltage starters
FUSE TYPE	Flush end BKN/Type K Indicator for Micro
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□	
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk250917en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□