Eaton 170M5467

Fuse-link, high speed, 1100 A, AC 600 V, size 2, aR, IEC, UL, single indicator

□□□□	
PRODUCT NAME	Eaton Bussmann series high speed square body fuse
CATALOG NUMBER	170M5467
UPC	051712261395
PRODUCT LENGTH/DEPTH	77 mm
PRODUCT HEIGHT	59 mm
PRODUCT WIDTH	51 mm
PRODUCT WEIGHT	309.25 g
COMPLIANCES	CE RoHS Compliant EAC
CERTIFICATIONS	IEC 60269-4 UL

Powering Business Worldwide

□□□□	
AMPERAGE RATING	1100 A
BREAKING CAPACITY	200 kA
FUSE INDICATOR	Centre fuse status indicator
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	2
RATED VOLTAGE AC	600 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	65.3 mm
CURRENT TYPE	AC
MOUNTING DIMENSION	M10
CLASS	Class aR
CLEARING (I2T)	1600000 at 660 V
WATT LOSSES	120 W
FUSE SHAPE	Square body, flush end contacts
PRE ARC (I2T)	245000
COLOR	None
INTERRUPT RATING	200 kAIC
FITTED WITH:	Type K Indicator for micro
CONSTRUCTION SIZE	2
MOUNTING METHOD	Flush
PACKAGING TYPE	Standard
VOLTAGE RATING	700 V (UL), 600 V (IEC)
TYPE	Fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
FUSE TYPE	Flush end BKN/Type K Indicator for Micro
FUSE SYSTEM (ACCORDING TO IEC 60269)	IEC 60269-4 flush end connections type A

□□	
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251012en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□