Eaton 170M2004

Fuse-link, high speed, 125 A, DC 750 V, compact size 1, 41 x 59 x 128 mm, aR, IEC, single indicator

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170M2004
PRODUCT LENGTH/DEPTH	130 mm
PRODUCT HEIGHT	59 mm
PRODUCT WIDTH	41 mm
PRODUCT WEIGHT	2294 g
COMPLIANCES	RoHS conform CE Marked

Powering Business Worldwide

□□□□

AMPERAGE RATING	125 A
BREAKING CAPACITY	85 kA
VOLTAGE TYPE	DC
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
RELEASE CHARACTERISTIC	Other
FUSE INDICATOR	Other
FREQUENCY RATING - MIN	45 Hz
FREQUENCY RATING - MAX	62 Hz
RATED SWITCHING CAPACITY	80 A
FUSE SIZE	1*
CLASS	Class aR
CLEARING (I2T)	9800 at 750 Vdc
WATT LOSSES	47 W
FUSE SHAPE	Square body, flush end contacts
PRE ARC (I2T)	2950
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	128 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	750 V
COLOR	None
INTERRUPT RATING	85 kA at 750 Vdc, 80 kA at 950 Vdc
CONSTRUCTION SIZE	Other
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	750 V
TYPE	Fuse
APPLICATION	• traction • third rail
FUSE SYSTEM (ACCORDING TO IEC 60269)	IEC 60269-4 flush end connections type A

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□