Eaton 170M2017

Fuse-link, high speed, 1000 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170M2017
PRODUCT LENGTH/DEPTH	180 mm
PRODUCT HEIGHT	92 mm
PRODUCT WIDTH	148 mm
PRODUCT WEIGHT	2.08 kg
COMPLIANCES	CE RoHS Compliant EAC
CERTIFICATIONS	IEC 60269-4

Powering Business Worldwide

□□□□	
AMPERAGE RATING	1000 A
BREAKING CAPACITY	110 kA
VOLTAGE TYPE	DC
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
RELEASE CHARACTERISTIC	Other
FUSE INDICATOR	Other
FREQUENCY RATING - MIN	45 Hz
FREQUENCY RATING - MAX	62 Hz
RATED SWITCHING CAPACITY	110 A
FUSE SIZE	23
CLASS	Class gR
CLEARING (I2T)	1973700 at 750 Vdc
WATT LOSSES	187 W
FUSE SHAPE	Square body, parallel bolted tags
PRE ARC (I2T)	476300
MOUNTING DIMENSION	Other
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	148 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	750 V
COLOR	None
INTERRUPT RATING	110 kAIC
CONSTRUCTION SIZE	3
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	750 V
TYPE	Fuse
APPLICATION	• traction • third rail
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□	
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251153en.pdf

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□