Eaton 170M2092

Fuse-link, high speed, 200 A, DC 2400 V, size 3, 83 x 93 x 268 mm, aR, IEC, single indicator

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170M2092
UPC	051712533973
PRODUCT LENGTH/DEPTH	268 mm
PRODUCT HEIGHT	93 mm
PRODUCT WIDTH	83 mm
PRODUCT WEIGHT	383.8 g
CERTIFICATIONS	IEC 60269-4

Powering Business Worldwide

□□□□

AMPERAGE RATING	200 A
BREAKING CAPACITY	100 kA
VOLTAGE TYPE	DC
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
RELEASE CHARACTERISTIC	Other
FUSE INDICATOR	Other
FREQUENCY RATING - MIN	45 Hz
FREQUENCY RATING - MAX	62 Hz
FUSE SIZE	3
CLASS	Class aR
CLEARING (I2T)	72561 at 2000 Vdc
WATT LOSSES	97 W
FUSE SHAPE	Square body, offset bolted tags
PRE ARC (I2T)	25667
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	246 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	2400 V
COLOR	None
INTERRUPT RATING	100 kAIC
CONSTRUCTION SIZE	1
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	2400 V
TYPE	Fuse
APPLICATION	• traction • third rail
FITTED WITH:	Double slot tags
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□