Eaton 170M2101

Fuse-link, high speed, 25 A, DC 1200 V, compact size 1, 39 x 66 x 164 mm, aR, IEC, single indicator

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170M2101
PRODUCT LENGTH/DEPTH	164 mm
PRODUCT HEIGHT	66 mm
PRODUCT WIDTH	39 mm
PRODUCT WEIGHT	2294 g
COMPLIANCES	CE Marked RoHS conform

Powering Business Worldwide

□□□□

AMPERAGE RATING	25 A
BREAKING CAPACITY	100 kA
VOLTAGE TYPE	DC
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
RELEASE CHARACTERISTIC	Other
FUSE INDICATOR	Other
FREQUENCY RATING - MIN	45 Hz
FREQUENCY RATING - MAX	62 Hz
RATED SWITCHING CAPACITY	150 A
FUSE SIZE	1*
CLASS	Class aR
CLEARING (I2T)	526 at 1200 Vdc
WATT LOSSES	8 W
FUSE SHAPE	Square body, offset bolted tags
PRE ARC (I2T)	173
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	139.5 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	1200 V
COLOR	None
INTERRUPT RATING	50 kAIC
CONSTRUCTION SIZE	Other
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	1200 V
TYPE	Fuse
APPLICATION	• traction • third rail
FITTED WITH:	Single slot tags
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□