Specifications



Photo is representative

Eaton LSE-11

Eaton LS-Titan Miniature DIN Electronic Limit Switch, Top Push Plunger, Polyamide PA66-GF25 encl, 0.2A max DC, Complementary PNP Open Collector, 0.2A at 24Vdc, Cage Clamps, 12-30 Vdc input, ±0.02mm accuracy, Short circuit protected

General specifications	
PRODUCT NAME	Eaton LS-Titan miniature DIN limit switch
CATALOG NUMBER	LSE-11
UPC	786685392530
PRODUCT LENGTH/DEPTH	1.22 in
PRODUCT HEIGHT	2.99 in
PRODUCT WIDTH	1.32 in
PRODUCT WEIGHT	0.1188 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Miniature DIN IEC limit switch

Product specifications

TYPE	LS-Titan
CONTACT RATING	0.2A at 24Vdc
ACCURACY	±0.02mm
ENCLOSURE MATERIAL	Polyamide PA66-GF25
PROTECTION	Short circuit protected
CONNECTION	Cage clamps
CONTACT CONFIGURATION	Complementary PNP open collector
SWITCH TYPE	Top push plunger Electronic contacts
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	IP66, IP67
MAXIMUM DC CURRENT	0.2 A
INPUT VOLTAGE	12-30 Vdc
LED INDICATOR	Status and error: single LED

Resources

CATALOGS	Sensing Solutions, Limit Switches, Volume 8, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - LSE-11

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.